

What temperature probes are compatible with Maretron's Temperature Monitor (TMP100)?

Article Number: 567 | Rating: 3.5/5 from 2 votes | Last Updated: Wed, Dec 16, 2015 3:44 PM

Maretron's Temperature Monitor (TMP100) has six channels for connecting up to six temperature probes. Two channels accommodate K-Type thermocouples and the remaining four channels accommodate thermistor type temperature probes. Maretron offers both thermocouple and thermistor probes as accessory items for the TMP100.

The K-Type thermocouple offered by Maretron is used for measuring exhaust gas temperature.

- <https://www.maretron.com/support/manuals/TP-EGT-1%20Installation%20Instructions%201.2.pdf>

Any K-Type thermocouple will work together with Maretron's TMP100. Search the Internet for “K-Type Thermocouple” and you can pick from hundreds of different probes.

Maretron also offers three different thermistor probes:

- <https://www.maretron.com/support/manuals/TP-AAP-1%20Installation%20Instructions%201.1.pdf>
- <https://www.maretron.com/support/manuals/TP-IP-1%20Installation%20Instructions%201.1.pdf>
- <https://www.maretron.com/support/manuals/TR3K%20Installation%20Instructions%201.2.pdf>

You can also build your own thermistor probes by using a thermistor that is compatible with the TMP100. Please see the documents within the “Attachment” section at the end of this article for compatible thermistor information (generally referred to as resistance/temp curve type “J” - 3000 ohms at 25°C). Please note that the TMP100 accuracy figure ($\pm 2^\circ$) used with thermistors is only valid between -20°C to 80°C or -4°F to 176°F.

Posted - Fri, Nov 30, 2012 6:05 PM. This article has been viewed 27960 times.

Online URL: <https://www.maretron.com/support/knowledgebase/phpkbv7/article.php?id=567>